MARK OUT II #1158201

Aerosol Vandal Mark & Graffiti Remover



Features:

- Heavy-duty, thick clinging gel will not run off
- No CFCs
- Effective on porous and non-porous surfaces
- Contains no ozone depleting chemicals
- Use indoors and outdoors
- Made in the USA

Description:

MARK OUT II heavy-duty, thick clinging gel that provides extended surface contact cleaning time with no CFCs. Cuts quickly through stubborn vandal marks without running or dripping. Effective on porous and non-porous surfaces. Removes spray paint, lipstick, ink, pencils, pens, crayons and more. Safe on brick, concrete, tile, formica, porcelain, baked enamels, chrome, walls, fences, glass, metal and most painted surfaces.



Applications:

- Crayon Pencil
- Lipstick
- Mimeo Ink

• Brick/Marble

- · Masking Tap
- Ball Point Inks
- Spray Paint

For Use On:

- Fiberglass
- Concrete

- Trucks Buses
- Enamels

DOT Placard: Not available.

Not available.

VOC Compliancy:

Sidewalks

• Formica

Porcelain

- Bridges
- Ceramic
- Chrome Varnishes
- Fences
- Signs

- Tile
- Glass
- Baked Enamel
- Washroom Walls
- · Public Buildings

Product Characteristics:

Appearance:		N.A.
Odor:		N.A.
Density VOC Less H2O & Exempts:		5.75318 lb/gal
VOC Regulatory(lb/gal):		3.36929 lb/gal
VOC Actual(g/l):		403.74200 g/l
VOC Regulatory(g/l):		403.74200 g/l
Density:		6.86189 lb/gal
Density VOC:		3.36929 lb/gal
% VOC:		49.10150%
Storage:	Protect from sunlight. Do not expose to	
	temperatures exceeding 50°C/122°F. Store in a	
	well-ventilated place. Store locked up.	
Transport Information:		
UN Number:		Limited Quantity
Proper Shipping Name:		Limited Quantity
Class:		Limited Quantity
Packing Group:		Limited Quantity

Directions:

Spray onto marks. Wait 5-10 minutes. Remove with clean cloth. If stubborn, repeat application. Allow to stand 30 to 60 minutes. If accumulation is heavy, remove with spatula, then re-spray. If extreme stubbornness is encountered, use stiff bristle brush and work into the stain. Spray on again wipe off again. Use clean brush or cloth.

*Care should be exercised when used on synthetic surfaces which are susceptible to solvent damage (asphalt tile, rubber, some paints and some plastics).

Not recommended on flat or semi-gloss painted surfaces. Pretest in hidden area if uncertain.

Pictograms:









Signal Word: DANGER.



Personal Protective Equipment Required:

