

MOLY-LUB BULK II #2137005

Methylene Chloride- Free Dry Anti-Seize Lubricant



Features:

- Reduces friction and wear
- Non-chlorinated, non-corrosive, non-conductive
- Temperature Range -40°F to +662°F
- Adheres to metal, glass, rubber and most plastics
- Resists pressures up to 250,000 psi
- Resists dust and abrasive particles
- Will not wipe off easily—chemically attracted to metal
- Permits immediate use of chain or gear after application
- Will not run off part to which applied, requires less frequent lubrication
- Can be used at higher temperatures and will not carbonize
- Withstands water, oils, alkalis and most acids
- Replaces graphite
- Cleaner application



Description:

MOLY-LUB BULK II is a methylene chloride free dry film lubricant offering superior, long-lasting performance. Molybdenum graphite anti-seize dry coating resists dust and abrasive particles. Withstands water, oil, alkalis and most acids. Forms a strong bond to metal—will not wipe off easily. May be used at higher temperatures—will not carbonize. Formula is more readily accepted by safety directors. May be used as a release agent.

For Use On:

- Lathe Bed & Rails
- Pipe Threads
- Road Equipment
- Pump Assemblies
- Door, Locks & Hinges
- Turbines
- Oil Drilling Equipment
- Chains & Sprockets

For Use By:

- Foundries
- Automotive Plants
- Sewing Trades
- Steel Mills
- Machine Shops
- Vehicle Maintenance
- Chemical Plants
- Shipyards
- Paper & Corrugated Converting
- Marine, Oil Fields & Mining Operations

Product Characteristics:

Appearance:	Black Liquid
Odor:	Solvent odor
Evaporation Rate:	> 1
Vapor Pressure (mm Hg):	77.3 @ 77°F (25°C)
Vapor Density (AIR=1):	4.5
Relative Density (H2O=1):	0.830 @ 77°F (25°C)
Solubility(ies):	Miscible
pH:	Not applicable
Flammability(solid/gas):	Flammable liquid
Toxicity:	100 ppm OSHA PEL
Wetting Ability:	None.
Storage Stability:	1 Year +
Cold Stability:	0°F
% Volatile By Volume:	>90%
Biodegradability:	No
Storage:	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry area. Away from sources of ignition or excessive heat. Wash hands after use.
Transport Information:	
UN Number:	UN 1993
Proper Shipping Name:	Flammable Liquid, N.O.S.
Class:	3
Packing Group:	II

Directions:

Shake or mix container well before using. Clean surface thoroughly. Apply a thin, even film by spraying or brushing. Thick coats decrease efficiency. Dries in 1 to 3 minutes. Allow to cure 30 minutes before exposing to water.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

Yes.