# XL 866 #1719

## **Aerosol Chain & Cable Lube**



#### Features:

- Fortified with Moly & PTFE
- Contains no chlorinated solvents or ozone depleters
- Penetrates for fast setup
- · Resists throw off
- Special valve for precise control and elimination of overspray
- Water and acid resistant
- Lubricates and reduces friction
- Ideal for chains, cables and moving assemblies
- Made in USA

# **Description:**

XL 866 is a mixture of penetrants, anti-oxidants, oils and greases for use on chains, cables and wire ropes. Fortified with both molybdenum disulfide and PTFE, the formula provides superior lubricity, protection, longevity and temperature resistance. Penetrates deep inside the core of wire rope to provide superior lubrication at the point of greatest stress. Using this product prevents metal-to-metal contact and reduces friction, heat, stress and wear during operation. May be used under widely varying climatic conditions and will not break down under heat, stress and prolonged use.



## **Applications:**

- Chains & Cables
- Chain Saws
- Sprockets

- Drive Chains
- Hoist Chains
- Drag Chains

- Roller Assemblies
- · Conveyer Chains
- Wire Ropes

#### For Use By:

- Factories
- Industrial Plants
- Mining Operations
- Bottling Companies
- Food Processing Plants
- Manufacturing Plants
- Hotels/Motels

Limited Quantity

Limited Quantity

Limited Quantity

• Breweries

- · Industrial Rendering
- Military Facilities
- Steel Mills
- Canneries

## **Product Characteristics:**

Proper Shipping Name:

Class:

Packing Group:

100000			
Appearance:		N.A.	
Odor:		N.A.	
Viscosity:		N.A.	
Flash Point:		N.A.	
pH:		N.A.	
Density VOC Less H2O & Exempts:		3.08604 lb/gal	
VOC Regulatory(lb/gal):		2.52614 lb/gal	
VOC Actual(g/l):		302.70700 g/l	
VOC Regulatory(g/l):		302.70700 g/l	
Density:		7.36263 lb/gal	
Density VOC:		2.52614 lb/gal	
% VOC:		34.31020%	
Storage:		n sunlight. Do not expose to	
	temperatures exceeding 50°C/122°F. Store		
	locked up.		
Transport Information:			
UN Number:		Limited Quantity	

## Directions:

SHAKE WELL BEFORE USE. Hold can 6-10 inches from surface to be lubricated and spray liberally.

## Pictograms:







Signal Word: DANGER.

### **Personal Protective Equipment Required:**



**VOC Compliancy:**Not for sale in CA, CT, DE, MD, NH & UT.

**DOT Placard**: Not available.