

QUIK-STIK #195811

General Purpose Adhesive



Features:

- Wide web spray
- Maximum strength formula
- Rapid setting & quick dry time
- Dries clear in 15 minutes
- Ideal for uneven or porous surfaces
- Suitable for use where high temperatures may be encountered
- Solids 18-20%
- No CFCs
- VOC compliant



Description:

QUIK-STIK is a high-performance aerosol adhesive offering rapid setting and quick dry time. Formulated to totally dry clear within 15 minutes. This adhesive is ideal for use on uneven or porous surfaces. This formulation works extremely well on surfaces such as: paper, cardboard, wood, leather, carpet backings, fabrics, most plastics, glass, and many other substrates. QUIK-STIK is suitable where high temperature may be encountered as well as uses where a clear, flexible, non-wrinkling, waterproof bond is desired.

Applications:

- Paper
- Cardboard
- Carpet Backings
- Most plastics
- Wood
- Leather
- Fabrics
- Glass

Product Characteristics:

Appearance:	Clear spray/mist
Physical State:	Liquid
Odor:	Solvent
VOC content (wt.%):	55
Solubility(water):	Insoluble
Relative Density:	0.8
Flash Point:	< 0°F (liquid portion)
pH:	Not applicable
Propellant:	Hydrocarbon
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable
Class:	2.1
Packing Group:	-

Directions:

Shake container well before using. This product works best at room temperature. Hold can 6-8 inches from surface to be covered. Apply even coats. Do not concentrate in one spot.

Permanent Bonds: Spray both surfaces and allow 2 minutes for drying. Bond with firm pressure. When finished spraying invert can and spray until tip is clear of adhesive. If tip clogs soak for 60 seconds in degreasing solvent.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

Yes.