

SLITHER - VOC COMPLIANT #1185001

Aerosol Creeping Lubricant



Features:

- Loosens frozen metal parts
- Harmless to metal
- Prevents rust
- Professional results every time
- Removes rust and gummed oil
- VOC compliant



Description:

SLITHER VOC COMPLIANT is a reliable penetrating oil that will produce professional results every time. The nanotechnology used in the production of this product allows it to creep into the tiniest spaces to loosen rusted and frozen parts. It can dissolve rust, lubricate, clean and prevent further rust build-up. It is also great at displacing moisture and can be used as a cutting oil.

Applications - Loosens:

- Studs
- Shafts
- Bearings
- Pulleys
- Guns
- Pipe Threads
- Screws, Nuts & Bolts
- Valve Guards
- Any corroded metal parts

Applications - Removes:

- Rust
- Gummed Oil
- Grease

Product Characteristics:

Appearance:	N/A
Odor:	N/A
Density VOC Less H2O & Exempts:	5.74195 lb/gal
VOC Regulatory(lb/gal):	0.75866 lb/gal
VOC Actual(g/l):	90.91000 g/l
VOC Regulatory(g/l):	90.91000 g/l
Density:	7.43054 lb/gal
Density VOC:	0.75866 lb/gal
% VOC:	10.21000%
Flash Point:	N/A
pH:	N/A
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Store locked up.
Transport Information:	
UN Number:	Limited Quantity
Proper Shipping Name:	Limited Quantity
Class:	Limited Quantity
Packing Group:	Limited Quantity

Directions:

Remove cap and shake can for 30 seconds. Spray at least 6-8 inches from part(s) to be lubricated. For tight or extremely small parts, insert extension tube into tip and then spray on part(s). Apply product as needed.

Note: Not for use on plastics. If contact does occur wipe off immediately.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

Yes.