

Scientifically formulated penetrating oil and rust dissolver containing micron size particles of PTFE and Moly. This super penetrant carries the PTFE and molybdenum disulfide particles into the threads, crevices, etc. These particles act as millions of tiny ball bearings to prevent seizing and galling while the parts are being removed. This product is designed to be used on all dismantling jobs throughout the plant, shop or wherever parts are frozen or hard to operate. Quickly loosens corroded nuts, studs, bolts, flanges and pipe joints.

DIRECTIONS FOR USE: Shake well. Remove protective cap and point spray opening in desired direction. Holding container 6-12 inches from surface to be treated, spray product liberally, saturating joints. Allow to set 5-10 minutes and break out. For extremely difficult jobs, saturate joints and allow to set 5-10 minutes, then tap lightly with a hammer and break out.

MODO DE EMPLEO: Agite bien antes de usar. Remueva la tapa protectora y apunte en la dirección deseada. Sostenga el contenedor de 6 a 12 pulgadas de la superficie que se va a tratar, rocíe el producto con libertad hasta saturar las juntas. Espere de 5 a 10 minutos para desatorar. Para trabajos extremadamente difíciles, sature las juntas y permita que actúe de 5 a 10 minutos, después golpee ligeramente con un martillo para desatorar.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. —No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IF SWALLOWED:** Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.



PELIGRO: Aerosol Extremadamente Inflamable. Contiene gas a presión; Puede explotar si se calienta. Puede ser fatal en caso de ingestión y entra por las vías respiratorias.

Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. —No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni quemé, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada. Lávese bien las manos después de manipular. **SI CAE EN LOS OJOS:** Enjuague cuidadosamente con agua durante varios minutos. Remueva lentes de contacto, si están presentes y fáciles de remover. Continúe enjuagando. Si persiste la irritación ocular: Consulte con un médico. **SI SE INGIERE:** Llame inmediatamente a un centro de control de venenos o un médico. NO induzca vomito. Elimine el contenido y envase de acuerdo con las ordenanzas locales, estatales, y reglamentos nacionales.



WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

ADVERTENCIA: Este producto puede exponerlo a sustancias químicas, incluyendo cumeno, que es conocido en el estado de California como causantes de cáncer. Para obtener más información vaya a www.P65Warnings.ca.gov.

CONTAINS (CAS#): Mineral Seal Oil (64741-44-2), Petroleum Distillates, hydrotreated light (64742-47-8), Propane/n-Butane (68476-86-8), Petroleum Distillate (64742-54-7), Ethyl Acetate (141-78-6). For more ingredient information visit www.procheminc.com.

**READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT
KEEP OUT OF REACH OF CHILDREN
FOR COMMERCIAL/INDUSTRIAL USE ONLY**

Scan for
Product
Info/SDS

1207901



An Exclusive Product of
PRO CHEM, INC.

1475 Bluegrass Lakes Parkway
Alpharetta, GA 30004
Procheminc.com



**PRO
CHEM**®

FREE ALL II

PENETRATING LUBRICANT



- **CONTAINS PTFE & MOLY**
- **FREES NUTS, BOLTS & STUDS**
- **LEAVES PERMANENT RUST PROTECTION**
- **QUICKLY LOOSENS RUSTED PARTS AND DISPLACES MOISTURE**

WARNING/ADVERTENCIA:
FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
AEROSOLÉS INFLAMABLES. CONTIENE GAS BAJO PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

**NET WT.
18 OZ. (510 g)**