# **PROTECT-O-SHIELD #1208001**

**Aerosol Corrosion Inhibitor** 

# Features:

- Non-drying formula
- Long term rust preventative lubricant
- Prevents rust and corrosion on metal parts •
- Excellent in protecting materials while in transit •
- Long protection for indoor storage
- Made in the USA

## **Description:**

PROTECT-O-SHIELD will prevent rust and corrosion on all metal parts. Affords long term protection for indoor storage. Excellent for protecting materials while in transit. A 2 or 3 mil coating will provide protection for indoor storage for up to 2 years. Film is transparent, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

#### **Applications:**

- Machine Parts
- Pipe Threads
- Cables

5

- Tools • Jigs Hoists
- Casting Stamped Metal Parts
- Pulleys
- Winches Riggings

## For Use On:

- Structural Steel & Wire
- Truck & Auto Bodies
- Air Conditioning Units
- Gutter & Downspouts
- Boats
- Oil Rigs

Ships

- Tanks & Piping
- Ducts & Culverts • Trailers & Docks
- Signs & Fencing
  - Road Equipment
- Dairy Equipment • Ornamental & Antique Metal

#### **Product Characteristics:**

Appearance:		Milky tan liquid
Odor:		Oily
Viscosity:		Not determined
Evaporation Rate:		Not determined
Solubility(ies):		0%
Relative Density (H2O=1):		0.83 - 0.86 g/ml @ 77°F (25°C)
Flash Point:		Not determined
pH:		Not applicable
Storage:	Protect from sunlight. Do not expose to	
	temperatures exceeding 50°C/122°F. Store in a	
	well-ventilated place.	
Transport Information:		
UN Number:		UN1950
Proper Shipping Name:		Aerosols, Ltd. Qty.
Class:		2.1
Packing Group:		Not applicable.

#### DOT Placard:

Not available.

**VOC Compliancy:** Not available.

#### Directions:

Product is most effective when parts are clean and free of rust, scale or dirt. Remove protective cap. Point opening in spray tip towards part to be coated. Holding can 8 to 10 inches from part, spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface.

• Marine Equipment

• Farm Equipment

\*To remove the Protect-O-Shield, use mineral spirits, kerosene or a light solvent.

# Pictograms:

**Signal Word:** 

WARNING.

**Personal Protective Equipment Required:** 





