

# RTV SILICONES



## **ALUMI-SEAL** *Aluminum RTV Silicone Gasket Maker*

- Pressurized can means no caulking gun required
- Cured material stays flexible as low as -76°F
- Can be applied overhead or on sidewall joints without sagging or running off
- Remains watertight and weatherproof through years of exposure
- Temperature range of -76°F to 300°F and up to 400°F intermittently
- Resistant to rain, sleet, snow, sunlight and temperature extremes
- When fully cured and washed meets USDA standards

## **BEAD-O-MATIC** *Hi-Temp Red RTV Silicone Gasket Maker*

- 100% RTV Silicone - Industrial Strength
- Pressurized dispensing makes any size or shape gasket instantly
- Remains permanently flexible-temperature range -60°F to 650°F intermittent
- Temperature range -76°F to 450°F, intermittently up to 500°F
- Reduces inventory - eliminates the need to stock conventional gaskets
- Reduces downtime - gets equipment back in operation fast
- When fully cured and washed, meets USDA standards

## **BLUE SEAL** *Blue RTV Silicone Sealant*

- 100% RTV silicone
- Industrial strength
- Remains permanently flexible
- Temperature range -76°F to 300°F, intermittently up to 400°F
- Easy to use
- Will not shrink or sag
- When fully cured and washed, meets USDA standards

## **CLEAR SEAL** *Multi-purpose Clear RTV Silicone Adhesive/Sealant/Caulker*

- Temperature range from -76°F to 300°F, intermittently up to 400°F
- Convenient, easy to use
- Bonds to most materials
- Will not shrink or sag
- When fully cured and washed, meets USDA standards

## **HI-BEAD** *High-Temp Red RTV Silicone Gasket Maker*

- Oxygen sensor safe
- Instantly forms any size or shape gasket
- Remains permanently flexible from -60°F to 600°F
- 100% silicone rubber
- Unique pressure valve allows more control of the bead size and is easier to handle, requiring less finger fatigue
- Meets GM specifications for low-volatility
- When fully cured and washed, meets USDA standards

## **MECHANIC'S HELPER** *Low Volatile Black RTV Silicone Automotive Gasket Maker*

- Pressurized dispensing makes any size or shape gasket instantly
- Reduces inventory - eliminates the need to stock conventional gaskets
- Reduces downtime – gets equipment back in operation fast
- Save to use on oxygen sensitive equipped vehicles
- Meets GM and OEM Specifications
- Temperature range -76°F to 350°F, intermittently up to 392°F (200°C)
- When fully cured and washed, meets USDA standards

## **PRO SEAL** *Clear RTV Silicone Rubber Adhesive Sealant*

- 100% RTV silicone
- Industrial strength
- Tack-free in 10-20 minutes
- Temperature range -76°F to 300°F, intermittently up to 400°F
- Insulates, seals, bonds
- Remains flexible
- When fully cured and washed, meets USDA standards

## **SUPER SEAL** *Multi-purpose White RTV Silicone Adhesive/Sealant/Caulker*

- Pressurized packaging eliminates need for caulking gun
- Temperature range -76°F to 300°F, intermittently up to 400°F
- Insulates electrical components
- Seals remain watertight
- When fully cured and washed, meets USDA standards