

# CHAIN WORX #1268001

## Aerosol Chain & Cable Lubricant



### Features:

- Contains "Moly"
- Penetrates, lubricates
- Forms protective rust barrier
- Thick foam clings to gears, chains and wire ropes
- Recommended for use in severe climatic conditions
- Provides resistance to wear
- Extreme pressure capability
- Will not break down under high temperatures



### Description:

CHAIN WORX is a moly containing lubricant that protects parts which are exposed to harmful or corrosive elements. Lubricates and penetrates to protect against friction and wear. Thick foam that clings to vertical surfaces. As foam breaks, product penetrates into wire ropes, links, and roller mechanisms. Provides resistance to wear. Extreme pressure capability. Will not break down under high temperatures and forms a protective rust barrier.

### Applications:

- Gears
- Chains
- Cables
- Sprockets
- Power Drive Hoists
- Wire Ropes
- Motorcycles
- Bicycles
- Chain Saws
- Link & Roller Assemblies
- Material Handling Equipment
- Road and Construction Machinery

### Product Characteristics:

Appearance:	Liquid
Odor:	N/A
Viscosity, Kinematic:	<0.205 cm <sup>2</sup> /s (40°C)
Flash Point:	-29°C (closed cup)
Lower Explosion Level:	1.9%
Upper Explosion Level:	9.5%
Vapor Density:	1.55 (air = 1)
Vapor Pressure:	101.3 kPa (20°C)
Density:	6.59 lb/gal
Density VOC:	1.32 lb/gal
% VOC:	20.1%
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. Store locked up. Store in a well-ventilated place.
<b>Transport Information:</b>	
UN Number:	UN1950
Proper Shipping Name:	Aerosols
Class:	2.2
Packing Group:	N/A

### Directions:

1. Shake can vigorously for one minute after mixing ball begins to rattle.
2. Spray 8-10 inches from surface.
3. Allow to penetrate.
4. Second coat gives additional protection.

### Pictograms:



### Signal Word:

DANGER.

### Personal Protective Equipment Required:



### DOT Placard:

Not available.

### VOC Compliancy:

Not available.