UPPER CUT #2268801

Degreasing, Deodorizing & Declogging



Features:

- Citrus solvent degreaser and odor counteractant
- 95% Natural orange terpenes
- · Dilutes & rinses with water
- Highly concentrated citrus solvent formulation
- Non-acid, non-caustic, non-corrosive
- No petroleum distillates
- Pleasant citrus fragrance
- 100% active, emulsifying, concentrated degreaser for removing heavy oils, greases, lubricants and adhesives

Drains



Description:

UPPER CUT is derived from citrus products, this 100% active formulation has a wide range of applications. It will emulsify when diluted with water for powerful grease cutting action. It may also be diluted with petroleum distillates depending on the nature of the job.

Applications:Asphalt

plications:

· Grease Traps

Product Characteristics:

Appearance:		Clear Liquid
Physical State:		Liquid
Color:		Orange
Odor:		Orange
VOC content (wt.%):		95
Solubility (water):		Emulsifies
Relative Density:		0.8
Flash Point:		122°F
pH:		Not applicable
	Keep container tightly closed. Ground/bond	
conta	container and receiving equipment. Store	
locke	locked up in a well-ventilated place. Keep cool.	
Transport Information:		
UN Number: UN 2		319
		PENE HYDROCARBONS,
Name: N.O		S. (CONTAINS D'LIMONENE)
Class: 3		
Packing Group: III		

Directions:

For Odor Control: Add 1 oz. concentrate into 1 gallon of cold water. Spray directly to odor source or to control atmospheric malodors spray upward into the air.

For Cleaning and Degreasing Surfaces: Dilute 3 oz. to 4 oz. concentrate per gallon of water. Apply directly to surface. Let stand two to four minutes before rinsing with clear water.

For Drain Maintenance: Add 3 oz. to 4 oz. concentrate to each drain. Let stand 5 to 10 minutes. Flush with hot tap water.

For Grease Traps: Pour 5 oz. of concentrate daily into traps under 20 ft. capacity. Large traps use 8 oz. to 10 oz. Excellent deodorizing.

For Asphalt and Tire Mark Removal: Apply concentrate directly. Allow to stand 2 to 4 minutes. Agitate if necessary. Rinse with clear water.

NOTE: DO NOT USE CLAY-TYPE ABSORBENT MATERIALS TO RECOVER SPILLS. DO NOT MIX WITH ACIDS OR OXIDIZERS.

DOT Placard:

Not available.

VOC Compliancy:

VOC Compliant - non-compliant in CA only

Pictograms:







Signal Word: DANGER.

Personal Protective Equipment Required:



