

# POLY BRITE #2108

## Interlocking Polymer Floor Finish



### Features:

- Unsurpassed leveling, excellent initial gloss, gloss retention and durability
- Provides a deep, even shine that is easily maintained
- Withstands almost any abuse
- Resists black heel marks
- 20% non-volatile solids
- Rated "excellent" for leveling, gloss, film formation, water resistance, detergent resistance, removability and black heel mark resistance



### Description:

POLY BRITE is a tough, durable metal interlock floor finish which dries to a deep even shine that enables it to be easily maintained. It is a hard styrenated ag both high gloss and excellent durability. It may be used with conventional low-speed or mop/recoat programs and provides excellent burnishing response with no powdering or dusting when using high speed burnishing equipment.

### Applications:

- Vinyl/Linoleum Floors
- Rubber Floors
- Terrazzo
- All Resilient Floors

### Product Characteristics:

Appearance:	Emulsion
Physical State:	Liquid
Color:	White
Odor:	Characteristic
Boiling Point:	Not available
Vapor Pressure:	Not available
Solubility (water):	Complete
Relative Density:	1.04
Flash Point:	None
VOC Content (Wt.%):	0
pH:	8-9
Leveling:	Excellent
Fim Formation:	Excellent
Gloss	Excellent
Water Resistance:	Excellent
Detergent Resistance:	Excellent
Removability:	Excellent
Black Heal Mark Resistance:	Excellent
Storage:	Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Keep out of reach of children.
<b>Transport Information:</b>	
UN Number:	Not regulated.
Proper Shipping Name:	Not regulated.
Class:	Not regulated.
Packing Group:	Not regulated.

### Directions:

1. Thoroughly strip floor with a floor finish stripper.
2. Rinse floor thoroughly with clean water.
3. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss.
4. Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp water.

Coverage – 2,000 to 3,000 square feet per gallon depending on application and porosity of floor.

**Maintenance:** Dust, mop, sweep, or damp mop as necessary. This floor finish is designed for low maintenance and buffing and is recommended on a weekly basis. It may be dry buffed weekly or buffed in conjunction with the aid of a restorer if necessary. This high speed finish is not designed for daily buffing.

### Pictograms:



### Signal Word:

No signal word.

### Personal Protective Equipment Required:



### DOT Placard:

Not regulated.

### VOC Compliancy:

Not available.