

SLIP-EZ – NEW FORMULA #1268401

Aerosol Food Grade, Dry Silicone Spray



Features:

- Heat stable from -35°F to 350°F
- Non-chlorinated
- Stops sticking
- Safe on plastic
- Concentrated formula
- Reduces friction between moving parts even for metal-to-metal contact surfaces
- Parts last longer
- Clean, dry spray does not leave a sticky residue behind.



Description:

SLIP-EZ is a food grade, dry silicone spray designed to lubricate equipment used in the packaging and processing industry. Leaves a non-staining dry pure silicone film to lubricate moving parts, reducing friction and wear. Product is heat stable from -35°F to 350°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. Complies with FDA regulations, CFR Title 21, paragraph 178.3570 when fully cured. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

For Use By:

- Food Processing Plants
- Restaurants
- Machine Shops
- Apparel Manufacturing
- Auto/RV Repair Shops & Institutions
- RV Dealerships
- Hotels/Motels
- Accessory Manufacturing

Applications:

- Service Hinges
- Plastic Products
- Slicing Equipment
- Tank Closure Seals
- Cutting Tables
- Conveyors
- RV Slide Outs
- Gasket/Tank Closures

Product Characteristics:

Appearance:	Clear, colorless spray
Odor:	Solvent odor
Initial Boiling Point/Range:	Not Determined
Evaporation Rate:	>3 Fast
Vapor Pressure (mm Hg):	Not Determined
Vapor Density (AIR=1):	Not Determined
Solubility(ies):	Not Determined
Relative Density (H2O=1):	0.74 - 0.78 @ 77 °F (25 °C)
Flash Point:	<5°F TCC
pH:	N/A
Wetting Ability:	Slight
Toxicity:	400 ppm OSHA TLV
Detergency:	None
Propellant:	Hydrocarbon
Cold Stability:	0°F
Storage Stability:	1 Year +
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, Ltd. Qty.
Class:	2.1
Packing Group:	N/A

Directions:

Read cautions and directions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5–10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

Pictograms:



Signal Word:
DANGER.

Personal Protective Equipment Required:



DOT Placard:
Not available.

VOC Compliancy:
Not available.