# **BOLT BLASTER – NEW FORMULA #1266901**

## **Aerosol Super Powerful Penetrating Catalyst**



#### Features:

- Super powerful penetrating catalyst
- Stops squeaks fast
- Frees rusted and corroded parts
- Reduces friction and wear over a broad temperature range
- Forceful jet spray
- Leaves a long-lasting lubricating film to defend against rust and corrosion

#### **Description:**

BOLT BLASTER features a forceful jet spray and a powerful penetrating catalyst which help provide rapid penetration through rust and corrosion to free frozen parts. It reduces friction and wear over a broad temperature range and leaves a long-lasting lubricating film to defend against rust and corrosion. This product creeps and pulls itself up, around and into cracks, crevices and threads with powerful capillary action.



#### **Applications:**

- Bearings
- Lug Nuts
- Fasteners
- Locks
- Clamps
- Motors
- Gears
- Threaded Parts

N/A

N/A

- Pulleys
- Hinges
- Tools
- Starters

- Relays
- Linkages
- · Frozen Nuts and Bolts
- Screws
- Engine Parts
- Generators

#### **Product Characteristics:**

Appearance:

Odor:

|        | Flash Point:                                     |                        | N/A                         |  |
|--------|--|------------------------|-----------------------------|--|
|        | pH:  |                        | N/A                         |  |
|        | Density VOC Less H2O & Exempt:                   |                        | 4.16181 lb/gal              |  |
| ١      | VOC Regulatory(lb/gal):                          |                        | 4.07246 lb/gal              |  |
| ١      | VOC Actu   | ıal(g/l):              | 488.00300 g/l               |  |
| ١      | VOC Regulatory(g/l):                             |                        | 488.00300 g/l               |  |
|        | Density:   |                        | 6.91230 lb/gal              |  |
|        | Density VOC:                                     |                        | 4.07246 lb/gal              |  |
| •      | % VOC:   |                        | 58.91620%                   |  |
| -      | Storage: Protect from sunlight. Do not expose to |                        |                             |  |
|        |  |                        | exceeding 50°C/122°F. Store |  |
|        | locked up. Protect from su                       |                        | nlight. Store in a          |  |
|        |  | well-ventilated place. |                             |  |
| _      | Transport Information:                           |                        |                             |  |
| ı      | UN Number:                                       |                        | Limited Quantity            |  |
|        | Proper Shipping Name:                            |                        | Limited Quantity            |  |
| Class: |  |                        | Limited Quantity            |  |
|        | Packing Group:                                   |                        | Limited Quantity            |  |

#### **Directions:**

Saturate part to be loosened and allow product to penetrate for a moment before attempting to break free. For heavily encrusted pieces a wire brush may be used to help remove corrosion. Apply a light final spray to all parts prior to reassembly.

CAUTION: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

#### Pictograms:









## Signal Word:

DANGER.

### **Personal Protective Equipment Required:**





## **DOT Placard:**

Not available.

#### **VOC Compliancy:**

Not available.