

END CON #1302801

Cold Pipe Insulation Spray



Features:

- Durable, flexible and water resistant
- Durable finish may be painted or primed
- Water resistant coating prevents condensation and dripping
- Repairs wrap around pipe insulation, prolonging life

Picture Coming Soon

Description:

END CON is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard-to-reach areas. Expanding spray conforms to irregularly shaped surfaces.

Applications:

- Cold Water Pipes
- Valves and Fittings
- Metal Gutters
- Refrigeration Lines
- Condenser Lines
- Water Tanks
- Air Conditioning Lines
- Refrigeration Trucks

Product Characteristics:

Appearance:	Clear, colorless to slight tint spray.
Odor:	Alcohol
Viscosity:	Not Determined
Evaporation Rate:	Not Determined
Vapor Pressure:	Not Determined
Solubility(ies):	Miscible.
Relative Density (H ₂ O=1):	0.81 @ 77 °F (25 °C).
Flash Point:	Not Determined
pH:	Not Applicable
Storage:	Store in a cool, dry area. Protect from sunlight. Store in a well-ventilated area. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, sparks, open flames or hot surfaces. No smoking.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, Ltd. Qty.
Class:	2.1
Packing Group:	Not Available

Directions:

SHAKE WELL BEFORE USE. Remove dust and loose dirt from surface to be sprayed by wiping with clean, dry cloth. Cover surfaces under area to be treated to avoid overspray. Shake can vigorously. Continue shaking for one minute and occasionally during use. For proper adhesion apply only to dry surfaces. Hold can 8-10" from surface. Apply with a sweeping motion using several thin coats. Allow each coat to dry thoroughly for several minutes before applying a new coat. If product runs, can is too close to surface.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.

VOC Compliancy:

VOC Compliant - Yes



SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1302801	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	End Con	EMERGENCY TELEPHONE:	1-800-535-5053
PRODUCT DESCRIPTION:	Cold Pipe Insulation Spray	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable Aerosol: Category 1 Gases Under Pressure: Liquefied Gas Eye Irritant: Category 2A Specific Target Organ Toxicity (Single Exposure): Category 3	SIGNAL WORD: DANGER	SYMBOL:	  
---	--------------------------------------	----------------	---

HAZARD STATEMENTS:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS:

Keep away from heat, sparks, open flames or hot surfaces. No smoking. Do not spray on an open flame or other ignition source. **Pressurized container:** Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.

HAZARDS NOT OTHERWISE CLASSIFIED:

No additional information available.

3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Acetone	67-64-1	30-60%
Propane/Butane	68476-86-8	15-40%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists.

SKIN: Remove contaminated clothes. Wash skin thoroughly with soap and water for 15 minutes. Seek medical attention if irritation develops.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation develops. Never give anything by mouth to an unconscious person.

ACUTE HEALTH HAZARDS: May cause defatting and dermatitis of the skin. Causes eye irritation including redness, tearing, and pain. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CHRONIC HEALTH HAZARDS: May cause damage to the following organs: kidneys, liver, skin. May cause central nervous system (CNS) depression. Repeated or prolonged contact may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, alcohol foam, and water spray or fog.

UNSUITABLE FIRE EXTINGUISHING MEDIA: Water jets or streams.

UNUSUAL FIRE AND EXPLOSION HAZARDS: EXTREMELY FLAMMABLE. Contents under pressure. Exposure to temperatures above 122°F (50 °C) may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Vapors may form explosive mixtures with air. Vapors are heavier than air and can accumulate in low areas. Vapors may travel considerable distance to a source of ignition and flash back.

HAZARDOUS COMPOSITION PRODUCTS: Oxides of carbon and hydrocarbons.

SPECIAL FIRE-FIGHTING METHODS: Wear NIOSH approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

PERSONAL PROTECTIVE EQUIPMENT: Refer to section 8 for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Absorb with non-combustible material like vermiculite, sand or earth. Place waste in proper containers for waste disposal. Prevent spill from entering sewers, storm drains and natural waterways. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

7. Handling and Storage

SAFE HANDLING AND STORAGE:

Do not use or store near heat, open flames or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Store in a cool, dry area. Protect from sunlight. Store in a well-ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Do not use or store with strong oxidizers. Wash hands thoroughly after handling.

OTHER PRECAUTIONS:

Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITIES: Strong oxidizing agents and reducing agents.

8. Exposure Controls / Personal Protection

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	250 ppm
Propane/Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Use only in well-ventilated areas.

RESPIRATORY PROTECTION: Not required with normal use. If vapors are present or irritation is experienced, use NIOSH/MSHA approved respirator.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles.



ADDITIONAL MEASURES:

Avoid contact with skin, eyes or clothing. Avoid breathing spray. Wash hands thoroughly after handling. No smoking or open flames.

9. Physical & Chemical Properties

Appearance:	Clear, colorless to slight tint spray.	Flammability(solid/gas):	Extremely flammable aerosol.
Physical State:	Spray	Flammability Limit-lower (%):	Not Determined
Form:	Spray	Flammability Limit-upper (%):	Not Determined
Color:	Clear	Explosive Limit-Lower (%):	Not Determined
Odor:	Alcohol odor	Explosive Limit-Upper (%):	Not Determined
Odor Threshold:	Not Determined	Vapor Density:	Not Determined
pH:	Not Available	Vapor Pressure:	Not Determined
Melting/Freezing Point:	Not Determined	Relative Density:	0.81 @ 77 °F (25 °C).
Boiling Point/Range:	Not Determined	Solubility (water):	Miscible.
Viscosity:	Not Determined	Auto-Ignition Temp:	Not Determined
Flash Point:	Not Determined	Decomposition Temp:	Not Determined
Evaporation Rate:	Not Determined	Partition Coeff(n-octanol/water):	Not Determined

10. Stability & Reactivity Information

REACTIVITY:

None known.

CHEMICAL STABILITY:

Stable.

POSSIBILITY OF HAZARDOUS REACTIONS:

None known.

CONDITIONS TO AVOID:

Temperatures greater than 122 °F (50 °C) and sources of ignition. Avoid incompatible materials.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and hydrocarbons.

11. Toxicological Information

TOXICOLOGICAL INFORMATION:

Acetone (67-64-1): LD₅₀ (Oral, Rat) 5800 mg/kg; LD₅₀ (Oral, Mouse) 3000 mg/kg; LD₅₀ (Oral, Rabbit) 5340 mg/kg; LC₅₀ (Inhalation, Rat, 8h) 50100 mg/m³; LC₅₀ (Inhalation, Mouse, 4h) 44,000 mg/m³.

Propane (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L.

PRIMARY ROUTE OF ENTRY: Eyes, Inhalation, Skin

Eyes: Causes irritation, redness, tearing, pain.

Skin: May cause irritation, redness, dryness.

Inhalation: May cause respiratory tract irritation, dizziness, headaches, nausea, unconsciousness, central nervous system (CNS) depression.

Ingestion: Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting.

MEDICAL CONDITION AGGRAVATED:

Pre-existing conditions of the central nervous system (CNS). May aggravate existing eye and respiratory conditions.

ACUTE HEALTH HAZARDS:

May cause defatting and dermatitis of the skin. Causes eye irritation including redness, tearing, and pain. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CHRONIC HEALTH HAZARDS:

May cause damage to the following organs: kidneys, liver, skin. May cause central nervous system (CNS) depression. Repeated or prolonged contact may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis.

CARCINOGENICITY:

OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A.

12. Ecological Information**ECOTOXICITY:**

Acetone (67-64-1): LC₅₀ (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC₅₀ (*Daphnia magna*, 48h) 6100 mg/L; EC₅₀ (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC₅₀ (*Pseudomonas putida*, 16h) 1700 mg/L.

PERSISTENCE AND DEGRADABILITY:

This product is biodegradable.

BIOACCUMULATIVE POTENTIAL:

This product is not expected to bioaccumulate.

MOBILITY IN SOIL:

This product is mobile in soil.

OTHER ADVERSE EFFECTS:

None known.

13. Disposal Consideration**WASTE DISPOSAL:**

Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS:

Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

14. Transportation Information

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:**VESSEL (IMO/IMDG)**

PROPER SHIPPING NAME: Aerosols.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

15. Regulatory Information

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5,000 pounds.

SARA 311/312 HAZARD CATEGORIES: Flammable (gases, aerosols, liquids, solids). Gas under pressure. Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure).

SARA 313 REPORTABLE INGREDIENTS: This product does not contain any chemical components with known CAS numbers that exceed the threshold (*de minimis*) reporting levels established by SARA Title III, Section 313.

CLEAN WATER ACT: Acetone (67-64-1) is a hazardous substance.

STATE REGULATIONS: California Proposition 65: This product does not contain chemicals regulated by California Proposition 65.

Acetone (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA.

INTERNATIONAL REGULATIONS: No information available.

16. Other Information**DISCLAIMER:**

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed, or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

SHAKE WELL BEFORE USE

END CON is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard to reach areas. Expanding spray conforms to irregularly shaped surfaces.

DIRECTIONS: Remove dust and loose dirt from surface to be sprayed by wiping with clean, dry cloth. Cover surfaces under area to be treated to avoid overspray. Shake can vigorously. Continue shaking for one minute and occasionally during use. For proper adhesion apply only to dry surfaces. Hold can 8-10" from surface. Apply with a sweeping motion using several thin coats. Allow each coat to dry thoroughly for several minutes before applying a new coat. If product runs, can is too close to surface.

MODO DE EMPLEO: Remueva el polvo y suciedad de la superficie que se va a rociar. Cubra las superficies debajo de la superficie que se va a limpiar para evitar ser rociadas. Agite vigorosamente. Continuar agitando por un minuto y ocasionalmente mientras se usa. Para una adhesión apropiada, aplique solo a superficies secas. Sostenga el bote de 8 a 10 pulgadas de la superficie. Aplique con un movimiento de lado a lado haciendo varias capas delgadas. Permita que se sequen por varios minutos. Si el producto se corre, el bote está muy cerca a la superficie.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. Keep away from heat, sparks, open flames or hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.



PELIGRO: Aerosol extremadamente inflamable. Contiene gas bajo presión; puede explotar si se calienta. Causas irritación ocular grave. Puede provocar irritación respiratoria, somnolencia o mareos. Mantener alejado del calor, chispas, llamas abiertas o superficies calientes. -No Fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Envase a presión: No perforar ni quemar, incluso después de su uso. Proteger de la luz solar. No exponer a temperaturas superiores a 50°C/122°F. Almacenar en un lugar bien ventilado. Lávese bien las manos después de manipular. Use protección para los ojos. En caso de contacto con los ojos: enjuagar cuidadosamente con agua durante varios minutos. Quite los lentes de contacto, si están presentes y son fáciles de hacer. Continúe enjuagando. Si la irritación de los ojos persiste: busque atención o asesoramiento médico. Evite respirar nieblas, vapores o aerosoles. Úselo únicamente al aire libre o en un área bien ventilada. Si se inhala: Lleve a la persona al aire libre y manténgala cómoda para respirar. Llame a un centro de intoxicaciones o a un médico si no se siente bien. Deseche el contenido y el contenedor de acuerdo con las regulaciones locales, estatales y federales.

CONTAINS (CAS#): Acetone (67-64-1), Propane (74-98-6), Butane (106-97-8), Ethyl Acetate (141-78-6). Stearic Acid (57-11-4).

Scan for Product
Info/SDS
1302801



An Exclusive Product of
PRO CHEM, INC.
1475 Bluegrass Lakes Parkway
Alpharetta, GA 30004
procheminc.com
1-800-241-8180



**PRO
CHEM**®

END CON

COLD PIPE INSULATION SPRAY



**DURABLE • FLEXIBLE
WATER RESISTANT**

DANGER/PELIGRO:

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION, DROWSINESS OR DIZZINESS. AEROSOL EXTREMADAMENTE INFLAMABLE. CONTIENE GAS BAJO PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA. CAUSAS IRRITACIÓN OCULAR GRAVE. PUEDE PROVOCAR IRRITACIÓN RESPIRATORIA, SOMNOLENCIA O MAREOS.

**NET WT.
14 OZ. (397 g)**