USE JUST RITE TO:

REMOVE: Grease, Grime, Gum, Adhesives, Cravon, Tar

SILENCE SQUEAKING: Doors, Chairs, Hinges, Wheels, Windows, Rollers, Moving Parts

DISPLACE MOISTURE FROM: Relays, Switches, Distributors, Spark Plugs, Wet Engines

LOOSEN: Locks, Valves, Frozen Bolts, Rusted Parts, Pipe Fittings

PROTECT: Dies, Tools, Chrome, Firearms, Equipment, Instruments

DIRECTIONS: Spray area to be treated. Let soak for a few minutes then wipe. For best rust protection, do not wipe off. To remove even the most stubborn frozen bolts, spray JUST RITE on affected area then tap bolt lightly allowing product to remain a few minutes until bolt is loosened.

NOTE: Avoid overspray onto floors or other surfaces which may become hazardous when slippery.

DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause cancer.



If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection/face protection. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store locked up. Store in a well-ventilated place. Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

FIRST AID: ON SKIN: Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use. IF exposed or concerned: Get medical advice/attention. IN EYES: Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention. IF INGESTED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. INHALATION: Remove source of exposure or move person to fresh air and keep comfortable for breathing.

CONTAINS (CAS#):

MINERAL SEAL OIL (64742-46-7), MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC (64742-52-5), CO2 (124-38-9).

Scan for Product Info/SDS Product # 1275901

211 X 713

PRO01021



An Exclusive Product of:
Pro Chem, Inc.
1475 Bluegrass Lakes Parkway
Alpharetta, GA 30004
Procheminc.com
1-800-241-8180



JUST RITE

Penetrant, Lubricant and Demoisturant

- Dielectric Strength 60,000v
 - Squeak Stopper
 - Metal Protector
 - Moisture Displacer
 - Loosens Rusted Parts
- Contains No Fluorocarbons

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS

NET WT: 12.5 OZ (354 G)

7.406"