



# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>PRODUCT NUMBER:</b>	1275901	<b>COMPANY PHONE:</b>	1-800-241-8180
<b>PRODUCT NAME:</b>	Just Rite - Aerosol	<b>EMERGENCY TELEPHONE:</b>	1-800-535-5053
<b>PRODUCT DESCRIPTION:</b>	Aerosol Penetrant, Lubricant & Demoisturant	<b>INFOTRAC:</b>	1-800-535-5053
<b>COMPANY INFORMATION:</b>	<b>PRO CHEM, INC.</b> 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

## 2. Hazards Identification

### GHS CLASSIFICATION:

Aerosols - Category 1  
Gases Under Pressure Liquefied Gas  
Carcinogenicity - Category 1B  
Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

**SIGNAL WORD:**  
DANGER

### SYMBOL:



### HAZARD STATEMENTS:

H222 - Extremely flammable aerosol  
H229 - Contains gas under pressure; may explode if heated.  
H280 - Contains gas under pressure; may explode if heated.  
H350 - May cause cancer.

### PRECAUTIONARY STATEMENTS:

**General:** P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read label before use.  
**Prevention:** P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use. P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing, eye protection/face protection.  
**Response:** P308 + P313 - IF exposed or concerned: Get medical advice/attention.  
**Storage:** P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P405 - Store locked up. P410 + P403 - Protect from sunlight. Store in a well-ventilated place.  
**Disposal:** P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC):

No additional information available.

## 3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
MINERAL SEAL OIL	0064742-46-7	48% - 73%
MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	0064742-52-5	35% - 53%
CO2	0000124-38-9	2% - 4%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## 4. First Aid Measures

### EMERGENCY OVERVIEW

**EYES:** Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

**SKIN:** Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use. IF exposed or concerned: Get medical advice/attention.

**INHALATION:** Remove source of exposure or move person to fresh air and keep comfortable for breathing. If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor. Eliminate all ignition sources if safe to do so.

**INGESTION:** Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

No data available.

### INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

No data available.

## 5. Fire-Fighting Measures

**SUITABLE FIRE EXTINGUISHING MEDIA:**

Dry chemical, foam, carbon dioxide. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only. Do not direct a solid stream of water or foam into hot, burning pools this may results in frothing and increase fire intensity.

**UNSUITABLE FIRE EXTINGUISHING MEDIA:**

No data available.

**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:**

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Container could potentially burst or be punctured upon mechanical impact.

**SPECIFIC FIRE-FIGHTING PRECAUTIONS:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:** Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

**6. Accidental Release Measures****EMERGENCY PROCEDURE:**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

**PROTECTIVE EQUIPMENT:**

Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

**PERSONAL PRECAUTIONS:**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

**ENVIRONMENTAL PRECAUTIONS:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

**METHODS & MATERIALS FOR CONTAINMENT & CLEANUP:**

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

**7. Handling and Storage****GENERAL:**

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored.

**VENTILATION REQUIREMENTS:**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

**STORAGE ROOM REQUIREMENTS:**

Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them. Store at temperatures below 120°F.

**8. Exposure Controls / Personal Protection****OCCUPATIONAL EXPOSURE LIMITS:**

Chemical Identity	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
CO2	5000	9000			1			5000
MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	500	2000			1			
MINERAL SEAL OIL	500	2000			1			

Chemical Identity	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
CO2	9000	30000	54000		5000		30000	
MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC					(L)[N159](L)[N800]	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];		
MINERAL SEAL OIL					(L)[N159](L)[N800]	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];		

**PERSONAL PROTECTIVE EQUIPMENT:**

**Eye/Face Protection:** Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

**Skin Protection:** Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

**APPROPRIATE ENGINEERING CONTROLS:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

**9. Physical & Chemical Properties**

<b>Appearance:</b>	Not Available	<b>Flammability(solid/gas):</b>	Not Available
<b>Physical State:</b>	Mist/Spray	<b>VOC Composite Partial Pressure:</b>	Not Available
<b>Form:</b>	Aerosol	<b>VOC Regulatory(lb/gal):</b>	0.00000 lb/gal
<b>Color:</b>	Not Available	<b>VOC Actual(g/l):</b>	0.00000 g/l
<b>Odor:</b>	Not Available	<b>VOC Regulatory(g/l):</b>	0.00000 g/l
<b>Odor Threshold:</b>	Not Available	<b>Density:</b>	7.64481 lb/gal
<b>pH:</b>	Not Available	<b>% VOC:</b>	0.00000%
<b>Melting/Freezing Point:</b>	Not Available/ Not Available	<b>Density VOC:</b>	0.00000 lb/gal
<b>Low/High Boiling Point/Range:</b>	Not Available/ Not Available	<b>Density VOC Less H2O and Exempts</b>	3.13437 lb/gal
<b>Viscosity:</b>	Not Available	<b>Auto-Ignition Temp:</b>	Not Available
<b>Flash Point</b>	Not Available	<b>Lower/Upper Explosion Level:</b>	Not Available/ Not Available
<b>Flash Point Symbol:</b>	Not Available	<b>Vapor Pressure/Vapor Density:</b>	Not Available/ Not Available
<b>Evaporation Rate:</b>	Not Available	<b>Solubility (water):</b>	Not Available

**10. Stability & Reactivity Information****CHEMICAL STABILITY:**

Stable under normal storage and handling conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS/POLYMERIZATION:**

Will not occur.

**CONDITIONS TO AVOID:**

Avoid heat, sparks, flame, high temperature and contact with incompatible materials. Dropping containers may cause bursting.

**INCOMPATIBLE MATERIALS:**

Avoid strong oxidizers, reducers, acids, and alkalis.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

No data available.

**11. Toxicological Information**

**Likely Route of Exposure:** Inhalation, ingestion, skin absorption.

**Skin Corrosion/Irritation:**

Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

**Serious Eye Damage/Irritation:**

Eye contact may lead to permanent damage if not treated promptly. Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly.

**Respiratory/Skin Sensitization:**

Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity:**

Based on available data, the classification criteria are not met.

**Carcinogenicity:**

May cause cancer.

**Reproductive Toxicity:**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure:**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure:**

Causes damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:**

Based on available data, the classification criteria are not met.

**Acute Toxicity:**

If inhaled, may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heartbeats.

**Chronic Exposure:**

Based on available data, the classification criteria are not met.

**Likely Routes of Exposure:**

Inhalation, Ingestion, Skin contact, Eye contact

**Potential Health Effects – Miscellaneous:**

Based on available data, the classification criteria are not met.

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC

LD50 (Rodent - rat, Oral) : >5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rabbit, Administration onto the skin) : >2000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

**12. Ecological Information**

**ECOTOXICITY:**

Based on available data, the classification criteria are not met.

**PERSISTENCE AND DEGRADABILITY:**

No data available.

**BIOACCUMULATIVE POTENTIAL:**

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC.

Contains constituents with the potential to bioaccumulate.

**MOBILITY IN SOIL:**

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC.

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

**OTHER ADVERSE EFFECTS:**

No data available.

**13. Disposal Consideration**

**DISPOSAL INSTRUCTIONS:**

**WASTE DISPOSAL:** Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

**14. Transportation Information**

**DOT:** Ground Transportation: (Continental United States, Canada & Mexico): Limited Quantity

**IATA:** Shipping Name: Aerosols

UN/NA #: 1950

Hazard Class: 2.2

Required Placard: Limited Quantity

Marine Pollutant: No data available

**IMDG:** Not regulated for transport

**15. Regulatory Information**

CAS	Chemical Name	% By Weight	Regulation List
0064742-46-7	MINERAL SEAL OIL	48% - 73%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0064742-52-5	MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	35% - 53%	DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)
0000124-38-9	CO2	2% - 4%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA)

**16. Other Information**

**Glossary**

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESLEffects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; N.A. - Not Available; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

**DISCLAIMER:**

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed, or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty expressed or inferred, regarding the product described in this SDS shall be created or

inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.